

## 100% Solids Colorants

**Product Description:** Florock 100% Solids Colorant make pigmenting a variety of Florock Systems fast and easy. Available in 8 quart cases, these colorants allow for convenient job site tinting. Unlike traditional colorants, solvent-free, 100% Solids Colorants will not incorporate any solvent or slow the cure time of blended resin systems.

### Instructions for Use:

1. Always mix or mechanically shake the can of colorant prior to blending in resin. Using the Usage Rate Table, determine how much 100% Solids Colorant will be necessary. Remember to calculate the quantity of 100% Solids Colorant needed, based on the combined volume (A & B mixture) of a two component system.

2. When pigmenting a dual component system, blend the two components together per system instructions. Induct if necessary. Then add in the amount of 100% Solids Colorant as specified in the Usage Rate Table.

3. Blend well, using a low speed mechanical mixer for a sufficient to develop a homogeneous appearance.

### Florock 100% Solids Colorants are compatible with the following Florock Systems:

- Floropoxy 4700, 4750, 4805, 4860 & 4870
- Novolac
- Florothane CR
- Florocrete SL
- System 6500
- System 3700

*Note: Consult your Florock Representative for use with other Florock Systems.*

*Note: The pigmenting of clear resin systems may result in a change of their chemical resistant properties.*

**Please read material safety data before using product.**

### DISCLAIMER:

All statements and recommendations are based on experience we believe to be reliable. The use or the application of these products being beyond the control of the Seller or Manufacturer, neither Seller nor Manufacturer make any warranty, expressed or implied, as to results or hazard from its use. The suitability, risk and liability whatsoever of a product for an intended use.

**KEY: C - Consult Representative N - Not Recommended**

<p><b>100% Solids Colorant</b></p> <p>Use lesser amount of colorant indicated for applications over 16 mils or in multicoat applications.</p>		<p><b>System</b></p>	<p>Floropoxy 4700, 4750, 4805, 4860 &amp; 4870</p>	<p>Novolac Epoxy</p>	<p>FloroWear 7000 &amp; 7100</p>	<p>Florothane CR 250</p>	<p>Florothane CR One-Coat</p>	<p>Florothane MC Ultra 340 Ultra 100 &amp; MC 60</p>	<p>System 3700</p>	<p>FloroCrete SL</p>	<p>System 6500</p>
			<p><b>Typical Batch Size:</b></p>	<p><i>Gal</i></p>	<p>4</p>	<p>5</p>	<p>4.5</p>	<p>4</p>	<p>3</p>	<p>5</p>	<p>5</p>
<p><b>P/N</b></p>	<p><b>Color</b></p>	<p><b>Quarts of Colorant</b></p>									
M8-138QT	Light Grey		2-4	2-4	N	2	2	N	4	1	2-4
M1-067QT	White		2-4	2-4	N	2	2	N	4	1	2-4
M7-062QT	Sand Beige		2	2	N	1-2	1-2	N	4	1	2
M4-056QT	Green		1-2	1-2	N	1-2	1-2	N	4	1	1-2
M5-046QT	Smoke Blue		1-2	1-2	N	1-2	1-2	N	2	1	1-2
M5-045QT	Standard Blue		1-2	1-2	N	1-2	1-2	N	2	1	1-2
M5-047QT	Assembly Blue		1-2	1-2	N	1-2	1-2	N	2	1	1-2
M8-137QT	White Night Grey		1-2	1-2	N	1-2	1-2	N	2	1	1-2
M8-136QT	Standard Grey		1-2	1-2	N	1-2	1-2	N	2	1	1-2
M6-040QT	Tile Red	1-2	1-2	N	1-2	1-2	N	2	1	1-2	

**Consult your Florock Representative for assistance with calculating product quantities.**

**Note Colorants are not recommended for use with Aqua Prime or FloroCrete TL.**