

FloroTint Colorants

For Use with Florothane MC/HT

Product Description: FloroTint Colorants make pigmenting Florothane MC/HT High Gloss or Satin fast and easy. Available in cases containing eight quart-sized cans, each filled with 26.2 ounces of colorant*, they allow for convenient jobsite tinting. Unlike traditional colorants, zero VOC FloroTint adds no solvent to the blended resin system will not interfere with cure time and exudes no odor.

Instructions for Use:

1. Always mix or mechanically shake the can of colorant prior to blending in resin. Always use two cans of FloroTint per 4.5 gallon Florothane MC/HT Base Resin Kit.*

2a. High Gloss Pigmented Florothane MC/HT – Combine Part A and Part B. Add two cans of Florock FloroTint* into the standard size mixture of Parts A and B.* Mix Parts A and B and FloroTint, using a Jiffy mixer blade with slow speed drill. Blend well, using a low speed mechanical mixer until mixture has a homogeneous appearance.

2b. Satin Pigmented Florothane MC/HT – Combine Part A and Part B. Add two cans of Florock FloroTint* into the standard size mixture of Parts A and B. Mix Parts A and B and FloroTint, using a Jiffy mixer blade with slow speed drill. **After 30-60 seconds of mixing the liquids, slowly add the MC/HT Satin High Traffic Powder and continue mixing until a total of 3 minutes of mixing has been achieved.**

Part Number	Add Two 26.2 Ounce Cans to Each Standard Size Florothane MC/HT Resin Kit*
C6-006EA	Tile Red
C5-014EA	Standard Blue
C6-016EA	Bright Red
C4-022EA	Standard Green
C2-008EA	Safety Yellow
C8-008EA	Black
C8-003EA	Light Gray
C8-002EA	White Knight Gray
C8-001EA	Standard Gray
C7-010EA	Sand Beige
C1-001EA	White
C5-016EA	Smoke Blue

***Mini Kits** – Add 9.2 ounces of FloroTint to each 0.75 ounce Florothane MC/HT Resin Mini Kit. A small can of FloroTint will be included in the Mini Kit upon request.

3. Apply in accordance with Florothane MC/HT technical data sheet instructions, being sure to follow specific directions for either High Gloss or Satin installation. Be sure to use all pigmented product within 24 hours.

Note: The pigmenting of clear resin systems may result in a change of their chemical resistance properties.

Note: Consult your Florock Representative for assistance with calculating product quantities. All coverages are approximate. Applications vary.

FloroTint Colorants

DISCLAIMER: All preceding statements and recommendations are based on experience we believe to be reliable. The use or application of these products being beyond the control of the Seller or Manufacturer, neither Seller nor Manufacturer make any Warranty, expressed or implied, as to results or hazard from its use. The suitability, risk and liability of a product for an intended use shall be solely up to the User.

Please read Safety Data Sheet before using product.