

Product Identification

Section 1

Product name Floropoxy SL 4700 Part B Hardener
Part number U0-144
Synonyms Epoxy Resin Activator
Product usage Activator part B for epoxy floor coating
Company Florock Polymer Flooring
1120 W Exchange
Chicago, IL 60609
Phone 773-376-7132
Chemtrec 800-424-9300

Hazard Identification

Section 2

GHS Classifications Flammable liquids: Category 4,
Serious eye damage/irritation: Category 1,
Skin corrosion/irritation: Category 1,
Skin sensitization: Category 1,
Acute Toxicity (Oral, Dermal, Inhalation): Category 4,
Aquatic environment (Acute): Category 2,

Signal word **Danger**

Pictograms



Hazard statements H302 Harmful if swallowed
H314 Causes severe skin burns and eye damage
H317 May cause an allergic skin reaction
H318 Causes serious eye damage
H227 Combustible liquid
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335 May cause respiratory irritation
H411 Toxic to aquatic life with long lasting effects

Precautionary statements P210 Keep away from heat/sparks/open flames/hot surfaces
P280 Wear protective gloves/clothing/eye protection/face protection.
P301+P310 IF SWALLOWED Immediately call POISON

CENTER/doctor
 P361+P353 Take off immediately all contaminated clothing.
 P264 Wash thoroughly after handling.
 P271 Use only outdoors or in a well ventilated area.
 P273 Avoid release to environment.
 P280 Wear eye protection/face protection.
 P301+P312+P330 IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth.
 P305+P340+P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
 P403+P233 Store in a well ventilated place. Keep container tightly closed.

Additional hazard Information Percentage of mixture with unknown Acute Toxicity:
none

Composition Information of Ingredients Section 3

Component	CAS No.	Weight %
Phenyl Carbinol	100-51-6	20-50
Amine	15520-10-2	20-50
Epoxy Resin	25085-99-8	5-20

*Where a range is displayed or the exact percentage of the component in the composition has been withheld it is considered a trade secret.
 Ingredients not listed on this SDS are considered to be non-hazardous.*

First Aid Measures Section 4

General Consult a physician. Show the physician this SDS. Move out of dangerous area immediately.

Inhalation Move person to fresh air and breathe normally. If experiencing respiratory symptoms. Call POISON CENTER or doctor.

Eyes Rinse cautiously with water for several minutes. Remove contact lenses if present. If eye irritation persists get medical attention.

Ingestion Immediately call POISON CENTER or physician. DO NOT induce vomiting. Do not eat, taste, or ingest. Rinse mouth if person is conscious.

Skin Take off all contaminated clothing. Rinse skin with water. Wash with soap and water. If skin irritation or rash occurs get medical attention.

Most Important Symptoms/Effects
 Acute Skin irritation, burns, difficulty breathing, nausea, vomiting, gastritis
 Delayed Repeated exposure may cause skin irritation.

Fire Fighting Measures

Section 5

Extinguishing media	Use water spray, alcohol resistant foam, dry chemical or carbon dioxide.
Extinguishing methods	Water may be used to keep exposed containers cool, and to keep flammable structures wet.
Special protective equipment	Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.
Special hazards	Carbon Oxides
Important additional information	<p>Containers may explode upon exposure to excessive heat and fire situations.</p> <p>Water may be used to keep exposed containers cool, and to keep flammable structures wet.</p> <p>Do not enter fire area without proper protection because hazardous decomposition products may be present. Sealed containers may explode if overheated.</p>

Accidental Release Measures

Section 6

Personal precautions	<p><i>Protective equipment:</i> Protective respirator, safety goggles, and gloves. Ensure adequate ventilation. Avoid breathing dust.</p> <p><i>Emergency procedures:</i> Evacuate personnel to safe areas.</p>
Methods for clean up and disposal	Ventilate the contaminated area. Collect the material using absorbents or other equipment required by the size of the release. Decontaminate the area, collecting any cleaning and rinsing media for proper reclamation or disposal. Soak up with an absorbent and place in non-leaking containers. Seal tightly for disposal according to local and federal regulations.

Handling and Storage

Section 7

Precautions for safe handling	<p>As with any chemical product, use good laboratory/workplace procedures. Do not cut, puncture, or weld on or near the container. Use under well-ventilated conditions. Wash thoroughly after handling this product. Always wash up before eating, smoking or using the facilities.</p> <p>Avoid eye and skin contact. Avoid drinking, tasting, swallowing or ingesting this product. Wash contaminated clothing before reuse. Discard shoes contaminated with this product.</p> <p>Avoid formation of dust and aerosols. The potential for combustible dust formation should be taken into consideration before additional</p>
-------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

processing occurs, like sanding and grinding. Provide appropriate exhaust ventilation at places where dust is formed.

Conditions for safe storage, including incompatibilities

Protect container from physical abuse. Keep the container tightly closed. Store in dry well-ventilated areas. Store this material away from incompatible substances (see section 10). Do not store in open, unlabeled or mislabeled containers. Do not reuse empty containers.

Exposure Controls/Personal Protection

Section 8

Component	CAS#	ACGIH/TLV	OSHA/PEL	*V/P
Phenyl Carbinol	100-51-6	1.230 mg/kg	2.000 mg/kg	0.1
Amine	15520-10-2	N/D	N/D	130
Epoxy Resin	25085-99-8	N/D	N/D	N/D

**Vapor Pressure limit*

Engineering Controls

Ventilation

Local and general ventilation controls recommended. Wash hands before breaks and at the end of the workday.

Personal Protective Equipment

Eye/Face protection

Protective safety goggles and/or face shield. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Polyvinyl or Teflon gloves are recommended. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Other protective considerations

Do not eat, drink, or smoke in areas where this material is used. Wash thoroughly after handling. Wash hands before eating, smoking, or touching the facial area.

Physical/Chemical Properties

Section 9

Physical state

Liquid

Appearance	Clear
Odor	N/D
Flashpoint	> 200 F
Boiling range	193 – 428 F
Vapor density	Heavier than air
Liquid density	Lighter than water
Volatiles volume	0 %
Evaporation Rate	n-Butyl Acetone
pH	N/D
Vapor pressure	N/D
Relative density (water = 1)	.991
Solubility (in water)	N/D
Partition coefficient	N/D
Auto Ignition temp	N/D

N.D. = No Data

Stability and Reactivity	Section 10
---------------------------------	-------------------

Chemical stability	Stable
Hazardous reactions	Will not polymerize
Conditions to avoid	Strong acids, oxidizers
Incompatibility	Strong acids, oxidizers
Hazardous decomposition products	Toxic fumes at decomposition temperatures. Such as carbon dioxide, carbon monoxide, oxides of nitrogen

Toxicological Information	Section 11
----------------------------------	-------------------

Routes of exposure	Inhalation, skin, eyes, ingestion
Symptoms of exposure	<p><i>Acute:</i> headache, dizziness, nausea, and loss of consciousness Irritation of skin, eyes, nose, throat, or lungs. May cause allergic skin reaction. High airborne concentrations of vapors resulting from heating, misting or spraying may cause irritation of the respiratory tract and mucous membranes.</p> <p><i>Chronic:</i> Ingestion may cause irritation. Severe eye irritation possibly resulting in permanent damage. Irritated mucous membranes, Dry skin</p>
Carcinogenicity	N/D

N/D = No Data Available

Acute Toxicity Values

The acute toxicity effects of this mixture have not been tested. Data on individual components are tabulated below:

Name	CAS#	Oral LD50	Dermal LD50	Vapor LC50
Phenyl Carbinol	100-51-6	1.230 mg/kg	2.000 mg/kg	N/D
Amine	15520-10-2	N/D	N/D	130
Epoxy Resin	25085-99-8	11400 mg/kg Rat > 2000 mg/kg Rabbit	11400 mg/kg Rat > 2000 mg/kg Rabbit	N/D

Ecological Information

Section 12

Keep out of sewers, drainage areas, and waterways. Report spills and atmospheric releases, as applicable, under Federal and State regulations.

Disposal Considerations

Section 13

Dispose of container and unused contents in accordance with federal, state, and local requirements for hazardous materials.

Transport Information

Section 14

DOT Proper Shipping	
Name:	
Packing Group:	
DOT Hazard Class:	
DOT UN/NA Number:	

Regulatory Information

Section 15

Contact manufacturer for information on specific territorial regulatory information.

Other Information

Section 16

NFPA/HMIS Rating

Health	3
Fire	1
Reactivity	1

Classification and hazards statements are listed according to the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS). Regulations in individual countries/regions may determine which classifications and hazard statements are applicable based on adopted hazard classes and categories. Precautionary statements are listed according to the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS) - Annex III. Regulations in individual countries/regions may determine which statements are required on the product label. See product label for specifics.

The information provided in this **Safety Data Sheet** is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal, and release. It is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.

Publication Date

2-02-2015